

Multi-Meter Assemblies - 208Y/120 Vac 3 phase 4 wire in, 1 phase 3 wire out					
Manufacture	Amperes Per Position	Number of Positions	Main Bus Rating in Amperes	Catalog Number	Description
Square D	225	2	800	EZML312225	Ringless design device, must be supplied with 5 - jaw lever bypass meter socket type HQ-5 and individual position barrel lock covers.
		3	800	EZML313225	
		4	800	EZML314225	

Multi-Meter Assemblies - 208Y/120 Vac 3 phase 4 wire or 240/120 Delta in, 3 phase 4 wire out					
Manufacture	Amperes Per Position	Number of Positions	Main Bus Rating in Amperes	Catalog Number	Description
Square D	225	1	1200	EZML331225	Ringless design device, must be supplied with 7 - jaw lever bypass meter socket type HQ-7 and individual position barrel lock covers.
		2	1200	EZML332225	
		3	1200	EZML333225	
		4	1200	EZML334225	
Siemens	100	1	1200	WML13100RJ	Ringless design device, must be supplied with 7 - jaw lever bypass meter socket type HQ-7 and individual position barrel lock covers.
		2	1200	WML23100RJ	
		3	1200	WML33100RJ	
		4	1200	WML43100RJ	
Siemens	225	1	1200	WML13225RJ	Ringless design device, must be supplied with 7 - jaw lever bypass meter socket type HQ-7 and individual position barrel lock covers.
		2	1200	WML23225RJ	
		3	1200	WML33225RJ	
		4	1200	WML43225RJ	
Eaton / Cutler - Hammer	225	1	1200	37MM120R12	Ringless design device, must be supplied with 7 - jaw meter socket and lever bypass. Must be supplied with individual position barrel lock covers.
		2	1200	37MM220R12	
		3	1200	37MM320R12	
		4	1200	37MM420R12	