

Multi-Meter Assemblies - 120/240 Vac 1 Phase 3 wire					
Manufacture	Amperes Per Position	Number of Positions	Main Bus Rating in Amperes	Catalog Number	Description
Square D	225	2	300	MPL32225	Ringless design device, must be supplied with 5 - jaw lever bypass meter socket type HQ-5 and individual position barrel lock covers.
		3	500	MPL53225	
		4	600	MPL64225	

Multi-Meter Assemblies - 120/240 Vac 1 Phase 3 wire in, 1 phase 3 wire out					
Manufacture	Amperes Per Position	Number of Positions	Main Bus Rating in Amperes	Catalog Number	Description
Siemens	225	1	1200	WML11225RJ	Ringless design device, must be supplied with 5 - jaw lever bypass meter socket type HQ-5 and individual position barrel lock covers.
		2	1200	WML21225RJ	
		3	1200	WML31225RJ	
		4	1200	WML41225RJ	
Square D	225	1	800	EZML111225	Ringless design device, must be supplied with 5 - jaw lever bypass meter socket type HQ-5 and individual position barrel lock covers.
		2	800	EZML112225	
		3	800	EZML113225	
		4	800	EZML114225	

Multi-Meter Assemblies - 208Y/120 Vac 3 phase 4 wire in, 1 phase 3 wire out					
Manufacture	Amperes Per Position	Number of Positions	Main Bus Rating in Amperes	Catalog Number	Description
Square D	225	2	800	EZML312225	Ringless design device, must be supplied with 5 - jaw lever bypass meter socket type HQ-5 and individual position barrel lock covers.
		3	800	EZML313225	
		4	800	EZML314225	
Siemens	200	1	1200	W2MM1200	Ringless design device, must be supplied with 5 - jaw meter socket and lever bypass. Must be supplied with individual position barrel lock covers.
		2	1200	W2MM2AB200	
		2	1200	W2MM2BC200	
		2	1200	W2MM2CA200	
		3	1200	W2MM3200	
		4	1200	W2MM4AB200	
		4	1200	W2MM4BC200	
Siemens	225	1	1200	WML12225RJ	Ringless design device, must be supplied with 5 - jaw meter socket and lever bypass. Must be supplied with individual position barrel lock covers.
		2	1200	WML22AB225RJ	
		2	1200	WML22BC225RJ	
		2	1200	WML22CA225RJ	
		3	1200	WML32225RJ	
		4	1200	WML42AB225RJ	
		4	1200	WML42BC225RJ	
Eaton / Cutler - Hammer	225	1	1200	35MM120R12	Ringless design device, must be supplied with 5 - jaw meter socket and lever bypass. Must be supplied with individual position barrel lock covers.
		2	1200	35MM220R12	
		3	1200	35MM320R12	
		4	1200	35MM420R12	