

Self Contained Single Phase One Meter Assemblies - 120/240 Vac 1 Phase 3 wire, service 200 Amperes or less			
Manufacture	Ampere Rating	Catalog Number	Description
Milbank	200	U3042-XL-QG-BLG	Ringless design device for OH/UG service, must be supplied with a 5 - jaw lever bypass meter socket
Durham	200	1005763	Ringless design device for OH/UG service, must be supplied with a 5 - jaw lever bypass meter socket
Eaton / Cutler-Hammer	200	UG-H4213C-CC-CH	Ringless design device for OH/UG service, must be supplied with a 5 - jaw lever bypass meter socket
	200	UG-E4213C-CC-CH	Ringless design device for OH/UG service, must be supplied with a 5 - jaw lever bypass meter socket
	200	1005763-CH	Ringless design device for OH/UG service, must be supplied with a 5 - jaw lever bypass meter socket
Square D	200	1005763-SQD	Ringless design device for OH/UG service, must be supplied with a 5 - jaw lever bypass meter socket
Midwest Electric Products	200	1005763-MEP	Ringless design device for OH/UG service, must be supplied with a 5 - jaw lever bypass meter socket
Siemens	200	S40405-015F	Ringless design device for OH/UG service only, must be supplied with a 5 - jaw lever bypass meter socket
Landis & Gyr	200	40405-015F	Ringless design device for OH/UG service only, must be supplied with a 5 - jaw lever bypass meter socket
Murray	200	RH173CRF	Ringless design device for OH/UG service only, must be supplied with a 5 - jaw lever bypass meter socket

Self Contained Single Phase One Meter Assemblies - 120/240 Vac 1 Phase 3 wire, 320 Ampere service ONLY.			
Manufacture	Ampere Rating	Catalog Number	Description
Siemens	320	S48105-83BU	Ringless design sidewire device for OH/UG service only, must be supplied with a 5 - jaw lever bypass meter socket
Landis & Gyr	320	48105-83BU	Ringless design sidewire device for OH/UG service only, must be supplied with a 5 - jaw lever bypass meter socket
Murray	320	RK178C-LI	Ringless design sidewire device for OH/UG service only, must be supplied with a 5 - jaw lever bypass meter socket
Milbank	320	U3885-X-BLG	Ringless design sidewire device for OH/UG service only, must be supplied with a 5 - jaw lever bypass meter socket